

## OSD-IMT955 STANDBY SAFETY VESSEL

#### **GENERAL INFORMATION**

Vessel Type	Standby Safety Vessel		
Class	Lloyds + 100 A1, + LMC, UMS		
L.O.A	55.20 m		
L.B.P	48.00 m		
Beam	12.70 m		
Rescue Draft	4.13 m		
Summer Load Draft	4.66 m		
Deadweight	881 tonnes		
Gross Tonnage	1433 tonnes		
Net Tonnage	429 tonnes		

#### CAPACITIES

Total Deck Area	200	
Deck Cargo	300	
Fuel Oil (Ship)	174	
Fuel Oil (Cargo)	230	
Potable Water (Ship)	140	
Potable Water (Cargo)	174	
Cargo FO Pumps	٦x	
Cargo PW Pumps	٦x	

# 0 m<sup>2</sup> 0 tonnes 4 m<sup>3</sup> 0 m<sup>3</sup> 0 m<sup>3</sup> 1 m<sup>3</sup> 75 m<sup>3</sup>/hr @ 100 mlc 75 m<sup>3</sup>/hr @ 100 mlc

#### ACCOMMODATION

Cabins

Accommodation

15 en-suite single cabins,7 fitted with Pullman BerthsShips Office, Mess room,Recreation Room, SmokingRoom, Gymnasium, Sauna

#### **PROPULSION CONFIGURATION**


Generators	4x	550 kW 440 v/3/60
DE System	SES Active Front End	
Main Propulsion	2x	750 kW Azimuth Thrusters
Bow Thruster	lx	450 kW Tunnel
Service speed	12.4	knots
Economical Speed	11.0	knots
Manoeuvrability	Joystick (3 positions)	

#### **EMERGENCY RESPONSE CAPABILITIES**

Rescue Craft	lx	6.5 m, 15 man FRC	
	lx	10.0 m Daughter Craft	
Mechanical Aids	lx	7 m Dacon Scoop	
Crane	٦x	Knuckle Boom Crane SWL	
		4.0/1.5 † @ 4.0/12.3 m	
Temporary Refuge	٦x	Rescue Basket	
Dispersant Capacity	5x	1 m <sup>3</sup> Plastic Tanks	
Towing Facilities	Cruciform Bollard at Transom		
Rescue Zones	lx	5 m Scrambling Nets (stbd)	
	٦x	7 m Dacon Scoop (port)	
Self-Drenching System	5	ltrs/m²/min	
Winching Zones	lx	Aft Deck	
	٦x	Focsle Deck	
Survivor Capability	UK G	roup B - 300 Survivors	
	Norw	ay - 260 Survivors	
	Denmark - 140 Survivors		
	Netherlands - 120 Survivors		



### **OSD-IMT955 STANDBY SAFETY VESSEL**



#### **HEAD OFFICE HOOFDDORP**

+31 255 545 070 info@osd-imt.com

#### UK OFFICES +44 1382 317 120 info@osd-imt.com

**SINGAPORE OFFICE** +65 6265 1154 info@osd-imt.com

