

OSD-IMT984(A) PLATFORM SUPPLY VESSEL

GENERAL INFORMATION

Vessel Type

Platform Supply Vessel DNV +1A1, Offshore Service Vessel -Supply, SPS, DYNPOS-AUTR, Fire Fighter I, Clean, SF, EO 84.65 m 75.70 m 18.00 m 7.60 m 6.30 m

CAPACITIES

Draft Design

I O A

IBP

Beam

Depth

| Total Deck Area | 810 | m ² |
|----------------------|------|----------------------------------|
| Ships Fuel Oil | 291 | m³ @ 96% Tank Volume |
| Cargo Fuel Oil | 764 | m ³ @ 96% Tank Volume |
| Potable Water | 669 | m ³ @ 96% Tank Volume |
| NLS (Mud, Brine etc) | 731 | m³ @ 96% Tank Volume |
| Base Oil | 183 | m³ @ 96% Tank Volume |
| Drill/Water Ballast | 1700 | m³ @ 96% Tank Volume |
| Dry Bulk | 305 | m³ @ 96% Tank Volume |
| Passive Anti-Roll | 205 | m³ @ 100% Tank Volume |

ACCOMMODATION

Complement Accommodation 48 persons on board
14 off single en-suite cabins
13 off, 2-person en suite cabins
2 off, 4-person en suite cabins
Ships Office, Mess Room
Lounge, TV Lounge, Offices, Gym

DYNAMIC POSITIONING

DP System compliant with DNV AUTR Notation

PROPULSION CONFIGURATION

Main Generators

Output

Output Emergency/ Harbour Generator

Output Voltage Propulsion Units Thrusters Service Speed Economic Speed Manoeuvrability

EQUIPMENT

Tugger Winches

Capstan Mooring

Windlass/Mooring

LIFE SAVING

1x SOLAS approved Fast Rescue Boat for 10 persons

2x Yanmar 6EY26LW Diesel Engines

2x Yanmar 6EY18LW Diesel Engines

driving DCG 114 K1-10 W Generators

1720 kW(e) @ 720 rpm 690/3/60

driving DCG 86 Ko-8 W Generators

680 kW(e) @ 900 rpm 690/3/60

1x MAN D2876 LF201 Diesel Engine

340 kW(e) @1800 rpm 440/3/60

1x Newage Stamford HCM 534C

2x 2000 kW Azimuth Propellers

3x 690 kW Bow Tunnel Thrusters

2x Electric Driven Tugger Winches

2x Hydraulic Driven Capstans

Each having a 10 t pull @ 0-20 m/min

Each having a 10 t pull @ 0-20 m/min

Each having a 12 t pull @ 0-12 m/min,

2x Electric Windlass/Mooring Winch

2 cable lifters, 2x warp heads

Generator

690 V/3 Ph/60 Hz

14.00 knots


12.00 Knots

DP & Joystick

- 2x 25 encl lifeboats, each suitable for 38 persons
- 4x 21 man life rafts



OSD-IMT984(A) PLATFORM SUPPLY VESSEL



HEAD OFFICE HOOFDDORP

+31 255 545 070

info@osd-imt.com

UK OFFICES +44 1382 317 120 info@osd-imt.com

SINGAPORE OFFICE +65 6265 1154 info@osd-imt.com

